

SURFACING BULL FLOATS



BULL FLOATS

The bull floats have been designed to perfect the concrete after the use of a vibrating screed by eliminating any imperfections on the surface of the wet concrete.

On floors where concrete is not vibrated, but a professional finish is required, these bull floats provide the perfect result.

The ENAR bull floats are available in 0.9m, 1.2m and 1.8metres. The handle is also available as fixed or oscillating depending on the job at hand. The new aluminium handle is also interchangeable with both models and can be extended.



ALUMINIUM HANDLE



FIXED BULL FLOAT



OSCILLATING BULL FLOAT



TECHNICAL DATA

OSCILLATING BULL FLOAT

MODEL	LENGTH (m)	WEIGHT (kg)	WIDE PROFILE (mm)
TRO 900 MG	0.9	4.6	205
TRO 1200 MG	1.2	5.8	205
TRO 1800 MG	1.8	7	205

FIXED BULL FLOAT

MODEL	LENGTH (m)	WEIGHT (kg)	WIDE PROFILE (mm)
TR 900 MG	0.9	4.4	205
TR 1200 MG	1.2	5.6	205
TR 1800 MG	1.8	6.8	205

ACCESSORIES

Brush kit for both oscillating and fixed bull floats

The brush can be installed for both fixed and oscillating bull floats. It allows the user to smooth and clean the concrete for a better finish.



MODEL	DESCRIPTION
BR AD	UNIVERSAL SUPPORT
B 900	BRUSH 0.9m
B 1200	BRUSH 1.2m
B 1800	BRUSH 1.8m