

Ideal for the maintenance of asphalt surfaces, laying porphyry and paving tiles, compacting any type of ground. The model features a unique and functional cover: the engine is completely protected against damages during transport and operation.

The cast iron plate and the cast engine support, which completely covers the vibrator unit, make the Batmatic CB1450 - CD1450 models strong and reliable over time.

The 14-liter water tank allows to work with less interruptions possible during asphalt compaction works.



Throttle control lever with fixed positions, to ensure productivity and reliability over time (diesel model).


**CB1450**

**CB1450 W**

**CD1450**

**CD1450 W**


(\*) engine not compliant to Stage 5 emissions standards, not available for EU market.


**15-25 cm**

**20 m/min**

**20°**

**90 Hz**

**16 kN**

MODEL	PLATE DIM	WEIGHT	FUEL	ENGINE	
CB1450	500 x 580 mm	89 kg 89 kg 90 kg	PETROL	Robin EX 17 Honda GX 160 Kohler SH 265	4,2 kW (5,7 HP) 3,6 kW (4,8 HP) 4,8 kW (6,5 HP)
CB1450 W with water tank	500 x 580 mm	92 kg 92 kg 93 kg	PETROL	Robin EX 17 Honda GX 160 Kohler SH 265	4,2 kW (5,7 HP) 3,6 kW (4,8 HP) 4,8 kW (6,5 HP)
CD1450	500 x 580 mm	102 kg 102 kg	DIESEL	Hatz 1 B20 Kohler 15LD225 (*)	3,7 kW (5,0 HP) 3,5 kW (4,7 HP)
CD1450 W with water tank	500 x 580 mm	105 kg 105 kg	DIESEL	Hatz 1 B20 Kohler 15LD225 (*)	3,7 kW (5,0 HP) 3,5 kW (4,7 HP)

### ACCESSORIES



Water system  
(14 litres)



Vulkollan® pad  
with brackets



Folding handle



Transport wheels  
(standard)