



The ANR/TNR range has a wide variety of pokers and transmissions, with various couplings.



**TECHNICAL DATA
TNR TRANSMISSIONS**

MODEL	LENGTH (m)	WEIGHT (Kg)
TNR6-25	6	8
TNR6-38	6	15.8
TNR6-48	6	15.8
TNR6-58	6	15.8
TNR6-70	6	15.8

*Other lengths available upon request



- » High quality transmission.
- » Extra protected Transmission where the transmission attaches to the poker. (For 48, 58 and 70mm models)
- » For different types of pins, please consult.
- » Axis rotation frequency: 3.000 r.p.m. Poker vibration frequency: 12.000 v.p.m.
- » Transmission diameter: 26mm for ANR25 poker and 36mm for the others (ANR 38-70).


ANR/TNR

**PENDULUM POKERS
AND TRANSMISSIONS**

**PETROL/
DIESEL/
ELECTRIC**


+ Adaptability

The TNR/ANR range adapts to all types of works, thanks to its indistinct operation with electric, petrol or diesel motors.



+ Versatility

Wide range of diameters and couplings adapt to all types of users.



+ Resistance

The greatest stress area is rubber reinforced. Robust mechanical system.

TECHNICAL DATA ANR POKERS

MODEL	DIAMETER (mm)	LENGTH (mm)	WEIGHT (Kg)	SPEED (r.p.m)	PERFORMANCE (m ³ /h)	TRANSMISSION
ANR25	25	350	1.2	16,000	10	TNR4-25/TNR6-25
ANR38	38	375	2.5	12,000	15	TNR4-38/TNR6-38
ANR48	48	445	4.3	12,000	25	TNR4-48/TNR6-48
ANR58	58	450	6.4	12,000	30	TNR4-58/TNR6-58
ANR70	70	510	7.5	12,000	35	TNR4-70/TNR6-70